

STICKCON

Wall Tiles Adhesive

VR

Type-2

POLYMER MODIFIED-WALL & FLOOR TILES ADHESIVE

Stiickcon Vitrified tiles adhesive is a grey cement-based, polymer modified, high quality tile adhesive recommended for fixing vitrified tiles, all Stones, Glass Mosaic tiles for Interior floors & walls application, Tile-on Tile, and for exterior floor application.

VR

AREAS OF APPLICATION

Stiickcon Vitrified tile adhesive is ideal for internal and external wall, tile-on-tile applications and floor applications of tiles.

FEATURES & BENEFITS

- Excellent adhesion to substrate
- Enhances durability
- High slip resistance
- Self-curing
- Easy-to-use

TECHNICAL DATA AS PER RELEVANT IS & ASTM STANDARDS

Bulk Density	1450-1550 Kg/m ³
Water Powder Ratio	25%
Pot Life	1 hour
Open Time	30 minutes
Adjustable Time	30 minutes
Usage Time Post Application	24 hours
Compressive Strength @ 28 Days	7-8 N/mm ²
Slip Resistance @ 20 Kg/Sq.m.	0 mm
Coverage @3mm Per Kg	4 Sq. ft.
Tensile Adhesion Strength @ 28 Days-IS 15477	Values
• Dry Condition	750-850 N
• Wet Condition	550-650 N
Shear Adhesion Strength	
• Dry Condition @ 24 Hour	3.5-4,5 KN
• Dry Condition @ 14 Days	10-10,5 KN
• Wet Condition @ 28 Days	4.5-5.5 KN
• Heat Ageing Condition @ 28 Days	4,5-5,5 KN

REFEREMCE STANDARD

IS 15477-2019, EN-1348

COVERAGE/ 20KG BAG

7.43 Sq.m @ 3mm




Shelf Life:

Shelf life of 12 months from the date of manufacturing.


AREAS OF APPLICATION

STICKCON Wall Tiles Adhesive - is a Polymer and Grey Cement base, high quality Wall tile adhesive, for fixing Stones & Vitrified / Glass Mosaic Tiles. Recommends for floor & wall Application on dry areas over Cementitious Substrate.(internal/External Application).

FOLLOW THE STEPS FOR APPLIATION



Clean the surface before use to remove Oil & Dust particles.




Mix Stïickcon Adhesive in water in the proportion of 1:0.25.




Mix thoroughly using stirrer for 2-4 minutes & wait for 5 minutes.



Apply adhesive and comb with notched trowel. For best results, apply on both substrate and tile (dual bonding).



Adhesive is to be used for fixing tiles only on cementitious surfaces.



Avoid adhesive to the dry during application.



CORPORATE OFFICE:

C-201, Swagat Rainforest-3, Kh Road, Sargasan, Gandhinagar-382 421. (Gujarat) INDIA

 Visit us : www.stickcon.com

Customer Care :  : +91 99090 90275  : info@stickcon.com

MANUFACTURING UNIT:

Plot No.: 262/2, Khakhariyavan Road, Villag. : Chikhalod, Ta.: Kapadeanj,

Dist. : Kheda, 387 640. (Gujarat) INDIA